MATERIAL SAFETY DATA SHEET

Date Printed: 03/03/2004
Date Updated: 09/08/2002

Version 1.5

Section 1 - Product and Company Information

Product Name TERT-BUTANOL, 99.3+% (TEBOL 99)

Product Number B85927
Brand ALDRICH

Company Sigma-Aldrich Street Address 3050 Spruce Street City, State, Zip, Country SAINT LOUIS MO 63103 US

Technical Phone: 314 771 5765

Emergency Phone: 414 273 3850 Ext. 5996

Fax: 800 325 5052

Section 2 - Composition/Information on Ingredient

Substance Name CAS # SARA 313 2-METHYL-2-PROPANOL 75-65-0 Yes

Formula C4H100

Synonyms Alcool butylique tertiaire (French) * Arconol *

t-Butanol * tert-Butanol * Butanol tertiaire (French) * tert-Butyl alcohol (OSHA) * t-Butyl hydroxide * 1,1-Dimethylethanol * Methanol,

trimethyl- * 2-Methyl-2-propanol *

2-Methylpropan-2-ol * NCI-C55367 * 2-Propanol,

2-methyl- * Trimethylcarbinol * Trimethyl methanol

RTECS Number: E01925000

Section 3 - Hazards Identification

EMERGENCY OVERVIEW

Flammable (USA) Highly Flammable (EU). Harmful.

Harmful by inhalation. Risk of serious damage to eyes.

Target organ(s): Central nervous system. Kidneys.

HMIS RATING

HEALTH: 2*
FLAMMABILITY: 3
REACTIVITY: 0

NFPA RATING

HEALTH: 2

FLAMMABILITY: 3 REACTIVITY: 0

*additional chronic hazards present.

For additional information on toxicity, please refer to Section 11.

Section 4 - First Aid Measures

ORAL EXPOSURE

If swallowed, wash out mouth with water provided person is

conscious. Call a physician.

INHALATION EXPOSURE

If inhaled, remove to fresh air. If not breathing give artificial respiration. If breathing is difficult, give oxygen.

DERMAL EXPOSURE

In case of skin contact, flush with copious amounts of water for at least 15 minutes. Remove contaminated clothing and shoes. Call a physician.

EYE EXPOSURE

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

Section 5 - Fire Fighting Measures

FLAMMABLE HAZARDS

Flammable Hazards: Yes

EXPLOSION HAZARDS

Vapor may travel considerable distance to source of ignition and flash back. Container explosion can occur under fire conditions. In advanced or massive fires the area should be evacuated and the fire should be fought from a remote explosion-resistant location.

FLASH POINT

51.8 °F 11 °C Method: closed cup

EXPLOSION LIMITS

Lower: 2.4 % Upper: 8 %

AUTOIGNITION TEMP

480 °C

FLAMMABILITY

N/A

EXTINGUISHING MEDIA

Suitable: Carbon dioxide, dry chemical powder, or appropriate foam. Use water spray to cool fire-exposed containers. Unsuitable: Water may be effective for cooling, but may not effect extinguishment.

FIREFIGHTING

Protective Equipment: Wear self-contained breathing apparatus and protective clothing to prevent contact with skin and eyes. Specific Hazard(s): Flammable liquid. Vapor may travel considerable distance to source of ignition and flash back. Emits toxic fumes under fire conditions.

Section 6 - Accidental Release Measures

PROCEDURE TO BE FOLLOWED IN CASE OF LEAK OR SPILL Evacuate area. Shut off all sources of ignition.

PROCEDURE(S) OF PERSONAL PRECAUTION(S)

Wear self-contained breathing apparatus, rubber boots, and heavy rubber gloves.

METHODS FOR CLEANING UP

Cover with dry-lime, sand, or soda ash. Place in covered containers using non-sparking tools and transport outdoors. Ventilate area and wash spill site after material pickup is complete.

Section 7 - Handling and Storage

HANDLING

User Exposure: Do not breathe vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated exposure.

STORAGE

Suitable: Keep container closed. Keep away from heat, sparks, and open flame.

Section 8 - Exposure Controls / PPE

ENGINEERING CONTROLS

Safety shower and eye bath. Use nonsparking tools. Mechanical exhaust required.

PERSONAL PROTECTIVE EQUIPMENT

Respiratory: Government approved respirator. Hand: Compatible chemical-resistant gloves. Eye: Chemical safety goggles.

GENERAL HYGIENE MEASURES

Wash thoroughly after handling. Wash contaminated clothing before reuse.

EXPOSURE LIMITS, RTECS

Country	Source	Type	Value
USA	ACGIH	TWA	100 PPM

USA MSHA Standard-air TWA 100 PPM (300 MG/M3)

USA OSHA. PEL 8H TWA 100 PPM (300 MG/M3)

New Zealand OEL

Remarks: check ACGIH TLV

USA NIOSH TWA 100 PPM STEL 150 PPM

EXPOSURE LIMITS

Country Source Type Value
Poland NDS 300 MG/M3
Poland NDSCh 450 MG/M3
Poland NDSP -

Section 9 - Physical/Chemical Properties

Appearance Physical State: Liquid

Color: Colorless

Property Value At Temperature or Pressure

Molecular Weight 74.12 AMU pH N/A

BP/BP Range 82 - 83 °C MP/MP Range 25 - 26 °C

Freezing Point N/A

Vapor Pressure 31 mmHg 20 °C

Vapor Density 2.5 g/l Saturated Vapor Conc. N/A

```
SG/Density
                       0.79 \, \text{g/cm}3
Bulk Density
                       N/A
Odor Threshold
                       N/A
Volatile%
                       N/A
VOC Content
                      N/A
                       < 0.1 %
Water Content
Solvent Content
                      N/A
Evaporation Rate
                       N/A
Viscosity
                       N/A
Surface Tension
                       N/A
Partition Coefficient N/A
Decomposition Temp. N/A
                       51.8 °F 11 °C Method: closed cup
Flash Point
Explosion Limits Lower: 2.4 %
                      Upper: 8 %
Flammability
                      N/A
Autoignition Temp
                      480 °C
Refractive Index
                       1.387
Optical Rotation
                      N/A
Miscellaneous Data
                      N/A
Solubility
                       N/A
N/A = not available
Section 10 - Stability and Reactivity
STABILITY
   Stable: Stable.
   Materials to Avoid: Strong oxidizing agents Copper, Copper alloys,
   Alkali metals, Aluminum.
HAZARDOUS DECOMPOSITION PRODUCTS
   Hazardous Decomposition Products: Carbon monoxide, Carbon dioxide,
   Peroxides.
HAZARDOUS POLYMERIZATION
   Hazardous Polymerization: Will not occur
Section 11 - Toxicological Information
ROUTE OF EXPOSURE
   Skin Contact: May cause skin irritation.
   Skin Absorption: May be harmful if absorbed through the skin.
   Eye Contact: Causes severe eye irritation.
   Inhalation: Harmful if inhaled. Material may be irritating to
   mucous membranes and upper respiratory tract.
   Ingestion: May be harmful if swallowed.
TARGET ORGAN(S) OR SYSTEM(S)
   Central nervous system. Kidneys. Liver. Bladder. Thyroid.
SIGNS AND SYMPTOMS OF EXPOSURE
   Can cause CNS depression. Exposure can cause: Gastrointestinal
   disturbances. Drying, cracking, or irritation of the skin.
TOXICITY DATA
   Oral
   Rat
   2743 mg/kg
   LD50
   Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and
```

```
Taste):Eye:Lacrimation. Lungs, Thorax, or
   Respiration: Respiratory depression. Gastrointestinal: Other
   changes.
   Inhalation
   Rat
   > 10,000 ppm
   LC50
   Remarks: Behavioral: Ataxia. Lungs, Thorax, or
   Respiration: Dyspnea. Lungs, Thorax, or Respiration: Pulmonary
   emboli.
   Intraperitoneal
   Mouse
   399 MG/KG
  LD50
  Remarks: Liver:Other changes.
   Intravenous
   Mouse
   1538 MG/KG
  LD50
   Oral
   Rabbit
   3559 \text{ mg/kg}
   LD50
   Remarks: Sense Organs and Special Senses (Nose, Eye, Ear, and
   Taste):Eye:Corneal damage. Cardiac:Pulse rate. Lungs, Thorax, or
   Respiration: Dyspnea.
   Skin
   Rabbit
   > 2000 \text{ mg/kg}
   LD50
   Remarks: Skin and Appendages: Skin: After systemic exposure:
   Dermatitis, other
IRRITATION DATA
   Skin
   Rabbit.
   0.5 ml
   Remarks: Mild irritation effect
   Eyes
   Rabbit
   0.1 \, \mathrm{ml}
   2.4H
   Remarks: Severe irritation effect
CHRONIC EXPOSURE - CARCINOGEN
   Result: This product is or contains a component that is not
   classifiable as to its carcinogenicity based on its IARC, ACGIH,
   NTP, or EPA classification.
   Species: Rat
   Route of Application: Oral
   Dose: 146 GM/KG
   Exposure Time: 2Y
   Frequency: C
```

Result: Tumorigenic: Neoplastic by RTECS criteria. Kidney, Ureter, Bladder: Kidney tumors. Species: Mouse Route of Application: Oral Dose: 1540 GM/KG Exposure Time: 2Y Frequency: C Result: Tumorigenic: Neoplastic by RTECS criteria. Endocrine: Thyroid tumors. NTP CARCINOGEN LIST Rating: Some evidence. Species: Mouse/rat Route: Drinking ACGIH CARCINOGEN LIST Rating: A4 CHRONIC EXPOSURE - TERATOGEN Species: Rat Dose: 2000 PPM/7H Route of Application: Inhalation Exposure Time: (1-19D PREG) Result: Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus). Species: Rat Dose: 3500 PPM/7H Route of Application: Inhalation Exposure Time: (1-19D PREG) Result: Specific Developmental Abnormalities: Musculoskeletal system. CHRONIC EXPOSURE - REPRODUCTIVE HAZARD Result: Overexposure may cause reproductive disorder(s) based on tests with laboratory animals. Species: Mouse Dose: 103 GM/KG Route of Application: Oral Exposure Time: (6-20D PREG) Result: Effects on Newborn: Stillbirth. Effects on Newborn: Growth statistics (e.g., reduced weight gain). Species: Mouse Dose: 135 GM/KG Route of Application: Oral Exposure Time: (6-20D PREG) Result: Effects on Newborn: Live birth index (# fetuses per litter; measured after birth). Species: Mouse Dose: 20240 MG/KG Route of Application: Oral Exposure Time: (6-18D PREG) Result: Effects on Fertility: Post-implantation mortality (e.g.,

dead and/or resorbed implants per total number of implants).

ACUTE ECOTOXICITY TESTS

Test Type: LC50 Fish

Species: Pimephales promelas (Fathead minnow)

Time: 96 h

Value: 6,140 mg/l

Test Type: EC50 Daphnia Species: Daphnia magna

Time: 48 h

Value: 933 mg/l

Test Type: IC50 Algae

Time: 72 h

Value: > 1,000 mg/l

ELIMINATION

Elimination: 99.9 %

Section 13 - Disposal Considerations

APPROPRIATE METHOD OF DISPOSAL OF SUBSTANCE OR PREPARATION

Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Observe all federal, state, and local environmental regulations.

Section 14 - Transport Information

DOT

Proper Shipping Name: Butanols

UN#: 1120 Class: 3

Packing Group: Packing Group II Hazard Label: Flammable liquid

PIH: Not PIH

TATA

Proper Shipping Name: Butanols

IATA UN Number: 1120 Hazard Class: 3 Packing Group: II

Section 15 - Regulatory Information

EU DIRECTIVES CLASSIFICATION

Symbol of Danger: F Xn

Indication of Danger: Highly Flammable. Harmful.

R: 11 20

Risk Statements: Highly flammable. Harmful by inhalation.

S: 9 16

Safety Statements: Keep container in a well-ventilated place.

Keep away from sources of ignition - no smoking.

US CLASSIFICATION AND LABEL TEXT

Indication of Danger: Flammable (USA) Highly Flammable (EU).

Harmful.

Risk Statements: Harmful by inhalation. Risk of serious damage

to eves.

Safety Statements: Keep container in a well-ventilated place. Keep away from sources of ignition - no smoking. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Wear eye/face protection. US Statements: Target organ(s): Central nervous system. Kidneys.

UNITED STATES REGULATORY INFORMATION

SARA LISTED: Yes DEMINIMIS: 1 %

NOTES: This product is subject to SARA section 313 reporting

requirements.

TSCA INVENTORY ITEM: Yes

CANADA REGULATORY INFORMATION

WHMIS Classification: This product has been classified in accordance with the hazard criteria of the CPR, and the MSDS contains all the information required by the CPR.

DSL: Yes NDSL: No

Section 16 - Other Information

DISCLAIMER

For R&D use only. Not for drug, household or other uses.

WARRANTY

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Inc., shall not be held liable for any damage resulting from handling or from contact with the above product. See reverse side of invoice or packing slip for additional terms and conditions of sale. Copyright 2004 Sigma-Aldrich Co. License granted to make unlimited paper copies for internal use only.